

XDS-1588

15" Interactive Room Panel

Part of the IDea Smart Workplace series —
Touch-enabled & status lights



Room Management for Corporate

Facility managers can
better manage the use of
space and go paperless



Space Management for High Eds

Help students quickly identify
the right meetings and locate
available study spaces



Single-Wire Installation

A single Ethernet cable
for connecting to power,
network, and data




LED Light Bars

A variety of programmable
colors to choose from to
indicate occupancy status



Built-In Flush Mount

All-in-one smart design
makes installation clean,
smart, and easy breezy



High Performance Processor

Powers smooth,
responsive, and vibrant
user experience



Instant On-Site Booking


Browse through room
schedules and make bookings,
or check-ins on-the-spot



Remote Device Management

Easily manage, monitor &
troubleshoot all
in-service room panels

I/O Ports for Extension



Technical Specifications

Display

- 15.6" IPS LCD panel
- 10 points capacitive multi-touch
- 300 nits maximum brightness
- 1920 x 1080 (Full HD) panel resolution
- Viewing angle (H/V): 178/178
- Programmable LED bar x 2

Internal Player

- Processor: Cortex-A17 1.8 GHz Quad-Core
- System memory: 2.0 GB
- Flash memory: 8 GB eMMC built-in

Video Format Supported

- H.264/AVC up to 1080p (1920 x 1080)
- H.265/AVC up to 1080p (1920 x 1080)
- MPEG-4 up to 1080p (1920 x 1080)
- MPEG-2 up to 1080p (1920 x 1080)
- MPEG-1 up to 1080p (1920 x 1080)
- VC-1 up to 1080p (1920 x 1080)

Image Format Supported

- JPEG up to 1920 x 1080
- PNG up to 1920 x 1080

Audio Format Supported

- MP3 up to 320 kbps

Content Management

- SignApps Express Utility
- 3rd party solution (optional license)

Open Standards Supported

- HTML5, JavaScript, and CSS
- W3C SMIL for cross-platform management
- W3C widgets for HTML delivery
- Android 7.1 API

HTML5 Support

- Widgets for calendar, clock, news, and web page integration
- HTML5 technologies including CSS and Javascript
- WebKit-based browser engine, same as Google Chrome™ and Apple Safari® browsers

Advanced Signage Features

- Remote commissioning
- AlwaysOn, AppLock to prevent unauthorized access
- StrongCache for continuous playback even when network is not available
- Multi-zone screen layout, transparent PNG overlay, and graphical scrolling ticker
- Auto-play starts playing scheduled contents automatically when power is re-established
- Automatic error recovery with built-in WDT
- Real-time clock with backup clock battery

Connectivity

- Front camera: 2MP
- Wi-Fi: 802.11 b/g/n
- Micro USB for ADB
- Ethernet RJ45
- USB 2.0 x 2
- Built-in 2 W stereo speakers x 2
- 3.5 mm analog stereo audio out
- Optional 3G / 4G mobile module via USB
- SD card slot, memory expendable to 16 GB / 32 GB / 64 GB (card replaces internal storage)

Mounting Options

- Built-in VESA MIS-D 100 mm x 100 mm mounting points

Available SKU

- XDS-1588 (IAdea standard)
- XDS-1588-A (with NFC & RFID embedded)
- XDS-1588-H (with HID embedded)

Supplied Accessories

- Power adapter and plug
- Flush mount bracket
- Quick guide

Power Requirement

- Input: 100 - 240 V, 50 - 60 Hz
- Output: 12 V, 2 A
- UL / CB certified power supplies
- Interchangeable connector system includes US plugs (optional for EU, UK, and AUS plugs)
- Power-over-Ethernet (PoE+) single-wire installation

Environmental

- Operating temperature: 0 to 40 °C
- Humidity: 10 to 85 % @ 40 °C non-condensing

Dimensions for Product & Package

- System dimension:
402 mm x 253 mm x 30 mm
(15.82" x 9.96" x 1.19")
- System weight: 1320 g (2.917 lb)
- Individual package dimension:
493 mm x 303 mm x 70 mm
(19.4" x 11.92" x 2.75")
- Individual package weight: 2000 g (4.42 lb)
- Units per outer carton: 5

Certifications

- CE / FCC / RoHS

Warranty

- 1-year limited parts & labor*
(varies based on region, contact sales for more details)

Contact

Lise-Meitner-Str. 1-7
24223 Schwentinental
Fon +49 431 221 303 20
info@christiansen-gmbh.de
www.christiansen-gmbh.de

